700XP Full Module Gas Fry Top, Mild S

	Electrolux
--	------------

Modular Cooking Range Line 700XP Full Module Gas Fry Top, Mild Steel

ITEM #		
MODEL #		
NAME #		
SIS#		
AIA#		



Modular Cooking Range Line

700XP Full Module Gas Fry Top, Mild Steel

371031 (E7FTGHSS00)

Full module gas fry top with smooth mild steel plate

371032 (E7FTGHSP00)

Full module gas fry top with 2/3 smooth and 1/3 ribbed mild steel plate

Short Form Specification

Item No.

To be installed on open base installations or bridging supports. Smooth cooking surface in mild steel. Suitable to be used with Natural or LPG gas. Temperature range from 200°C to 400°C. Removable drawer below the cooking surface for the collection of grease and fat. Exterior panels in stainless steel with Scotch Brite finish. One piece pressed work top in 1.5 mm thick stainless steel. Right-angled side edges to allow flush-fitting junction between units.

Main Features

- Unit to be mounted on open base cupboards, bridging supports or cantilever systems.
- Large drain hole on cooking surface permits the draining of fat into large 1,5 liter collector placed under the cooking surface.
- Large grease collection container available as optional accessory to be installed under top units over open base cupboard.
- Regulators with fixed high and low positions for precise control.
- Stainless steel high splash guard on the rear and sides of cooking surface. Splash guard can be easily removed for cleaning.
- Scrapers with smooth or ribbed blades included as standard.
- Piezo spark ignition for added safety.
- Temperature range of griddle from 200 °C to 400 °C.
- Gas appliance supplied for use with natural or LPG gas, conversion jets supplied as standard.
- IPX 4 water protection.

Construction

- Cooking surface in mild steel for optimum grilling results.
- Cooking surface to be completely smooth or 2/3 smooth and 1/3 ribbed.
- All exterior panels in Stainless Steel with Scotch Brite finishing.
- One piece pressed 1.5 mm work top in Stainless steel.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.

Optional Accessories

•	Scraper for smooth plate fry tops	PINC	164255
•	Draught diverter, 150 mm diameter	PNC	206132
•	Matching ring for flue condenser, 150 mm diameter	PNC	206133
•	4 wheels, 2 swivelling with brake (700/900XP). It is mandatory to install with base supports for feet/wheels.		206135
•	Support for bridge type installation, 800mm	PNC	206137
•	Support for bridge type installation, 1000mm	PNC	206138
•	Support for bridge type installation, 1200mm	PNC	206139
•	Support for bridge type installation, 1400mm	PNC	206140
•	Support for bridge type installation,	PNC	206141

APPROVAL:

1600mm




Modular Cooking Range Line 700XP Full Module Gas Fry Top, Mild Steel

 Flue condenser for 1 module, 150 mm diameter 	PNC 206246 □
 Water column with swivel arm (water column extension not included) 	PNC 206289 □
Water column extension for 700 line	PNC 206291 □
Chimney upstand, 800mm	PNC 206304 🖵
Right and left side handrails	PNC 206307 🖵
 Grease/oil kit container for 700 line frytops (half and module) and 900 line frytops (module) 	PNC 206346 □
 Base support for feet or wheels - 800mm (700/900) 	PNC 206367 □
 Rear paneling - 800mm (700/900) 	PNC 206374 🖵
• Rear paneling - 1000mm (700/900)	PNC 206375 □
 Rear paneling - 1200mm (700/900) 	PNC 206376 🖵
Chimney grid net, 400mm	PNC 206400 🖵
 Scraper for ribbed plate fry tops (only for 371032) 	PNC 206420 🖵
• Frontal handrail, 800mm	PNC 216047 🖵
 Frontal handrail, 1200mm 	PNC 216049 🗆
 Frontal handrail, 1600mm 	PNC 216050 🖵
• Large handrail - portioning shelf, 400mm	PNC 216185 🖵
• Large handrail - portioning shelf, 800mm	PNC 216186 🖵
• 2 side covering panels for top appliances	PNC 216277 🖵
 Pressure regulator for gas units 	PNC 927225 □





Modular Cooking Range Line 700XP Full Module Gas Fry Top, Mild Steel



\sim		
(-	а	C
\sim	c	-

Gas Power:

371031 (E7FTGHSS00) 47726 Btu/hr (14 kW) **371032 (E7FTGHSP00)** 47726 Btu/hr (14 kW)

Gas Type Option: LPG Gas Inlet: 1/2"

Natural gas - Pressure:

371031 (E7FTGHSS00) 7" w.c. (17.4 mbar)

LPG Gas Pressure:

371031 (E7FTGHSS00) 11" w.c. (27.7 mbar)

Key Information:

Cooking surface width:730 mmCooking surface depth:540 mmWorking Temperature MIN:200 °CWorking Temperature MAX:400 °CNet weight:70 kg

Shipping weight:

371031 (E7FTGHSS00) 90 kg **371032 (E7FTGHSP00)** 84 kg

Shipping height:

371031 (E7FTGHSS00) 520 mm 371032 (E7FTGHSP00) 540 mm Shipping width: 820 mm Shipping depth: 860 mm

Shipping volume:

371031 (E7FTGHSS00) 0.37 m³ **371032 (E7FTGHSP00)** 0.4 m³

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.



Modular Cooking Range Line 700XP Full Module Gas Fry Top, Mild Steel