Warewashing Green&Clean Hood Type Dishwasher with Drain Pump & Detergent Dispenser

| ITEM # | | |
|----------------|--|--|
| MODEL # | | |
| NAME # | | |
| SIS # | | |
| 313 # AIA # | | |
| AIA # | | |



Warewashing

Green&Clean Hood Type Dishwasher with Drain Pump & Detergent Dispenser

505070 (NHT8G)

Green & Clean Hood Type Dishwasher, Single skin hood with Drain Pump and Detergent & Rinse aid dispensers, 80racks/hour -400 V/3N/50 Hz

Short Form Specification

Item No.

Unit to be Electrolux Green & Clean upright hood type hot water rinsing dishwasher. Electrical characteristics to be 400 volts, three phase 50Hz operation, convertible to single phase on-site. Uses 2 liters of clean water per final rinse cycle. 84°C rinse temperature and pressure guaranteed by built in atmospheric boiler and built in rinse booster pump. Washing performance is guaranteed by a powerful 0.8 kW wash pump and upper and lower stainless steel revolving washing spray arms. 304 Stainless steel construction to include single skin hood, external, front and side panels, wash tank, tank filter plus wash and rinse arms. Unit shall be field convertible from straight to corner operation. The unit shall include drain pump, detergent and rinse aid dispenser pumps and is equipped with flexible fill hoses. Delivered on height-adjustable feet.

Main Features

- ETL-Sanitation approved (ANSI/NSF 3 sanitation standard) and DIN 10512 compliant.
- Requires only 2 liters of water per washing cycle thus ensuring low energy, water, detergent and rinse aid consumption.
- Built-in atmospheric boiler sized to raise incoming water to a minimum of 84 °C for sanitizing rinse. No external booster is required. Constant temperature of 84 °C throughout the rinsing cycle regardless of the network's water pressure.
- Unique temperature interlock guarantees required temperatures in both the wash and final rinse.
- Maximum capacity per hour of 80 racks or 1.440 dishes (High productivity mode) easy to switch to 63 racks or 1.134 dishes (ETL-Sanitation mode) by pressing a button.
- 45/84/150 seconds cycles (High productivity mode); 57/84/150 seconds cycles (ETL-Sanitation mode).
- Incorporated Soft Start feature to offer additional protection to more delicate items.
- Slanted wash arms to avoid detergent-filled wash water dropping on clean dishes after the rinsing phase, thus guaranteeing ideal washing results.
- Cycle may be interrupted at any time by lifting the hood.
- Automatic self-cleaning cycle and self-draining vertical wash pump and boiler to avoid bacteria proliferation.
- State-of-the-art electronic controls with built-in programming, self-diagnostics for serviceability and automatic interior self-cleaning cycle.
- Built-in rinse aid and detergent dispenser with automatic initial and continuous cycle loading for perfect result while minimizing service and maintenance needs.
- Boiler power setting from control panel to facilitate technician's operation when reducing total installed power, thus avoiding the need of machine opening.
- Three phase electrical connection, convertible to single phase on-site.
- IP25 protection against water jet, solid objects and small animals (larger than 6 mm).

Construction

- Heavy duty Stainless steel construction. Internal cavity as well as exterior panels are in 304 series Stainless steel.
- Pressed tank in front position to facilitate cleaning.
- Single skin hood supported by 3 springs to ensure smooth movement and guarantee operator safety.
- Specially designed Stainless steel wash/rinse arms and nozzles provide superior cleaning action.
- Revolving interchangeable Stainless steel wash/rinse arms above and below the rack, screw out for simple clean up.
- Pre-arranged for on-site HACCP implementation and Energy Management device.
- Element protection from dry fire and low water.
- Unit to include drain, detergent and rinse aid dispenser pumps

APPROVAL:



Included Accessories

| included Accessories | | | |
|--|--------------|--|--|
| 1 of Yellow cutlery container | PNC 864242 | | |
| 1 of Basket for 18 dinner plates - yellow | PNC 867002 | | |
| Optional Accessories | | | |
| Kit 8 plastic boxes for cutlery - yellow | PNC 780068 □ | | |
| 12lt external manual water softener | PNC 860412 🗆 | | |
| 8lt external automatic water softener | PNC 860413 🗆 | | |
| 20lt external manual water softener | PNC 860430 🗆 | | |
| HACCP printer kit | PNC 864002 □ | | |
| HACCP kit with cable for single skin hood type | PNC 864006 □ | | |
| Stainless steel inlet hose kit | PNC 864016 🗆 | | |
| Filter for partial demineralization | PNC 864017 🗆 | | |
| Kit to measure total and partial water hardness | PNC 864050 🗆 | | |
| Yellow cutlery container | PNC 864242 🗆 | | |
| CLEAR BLUE Filtering System kit for single skin hood type | PNC 864329 □ | | |
| Filter for total demineralization | PNC 864367 🗖 | | |
| Front control panel for single skin hood type dishwasher | PNC 864374 □ | | |
| ZERO LIME device kit with pump and air gap for hood type | PNC 864526 □ | | |
| Connecting kit for twin set manual hood type dishwasher | PNC 865264 □ | | |
| Kit 4 plastic boxes for cutlery - yellow | PNC 865574 🗆 | | |
| Basket for 6 trays 530x370 mm - red | PNC 866743 🗖 | | |
| Basket for 12 soup bowls - green | PNC 867000 □ | | |
| Basket for 18 dinner plates - yellow | PNC 867002 □ | | |
| Basket for 48 small cups or 24 cups - blue | PNC 867007 □ | | |
| Basket for bulk cutlery-capacity: 100 pieces - brown | PNC 867009 □ | | |
| Cover rack for small and light items (500x500 baskets) | PNC 867016 □ | | |
| Baskets for 25 tilted glasses (h 120 mm - diam 80PNC 867021 ☐ mm) - blue | | | |
| Basket for 16 vertical glasses (h 70 mm - diam 100 mm) - blue | PNC 867023 □ | | |
| Basket semi-professional 500x500x190mm | PNC 867024 🗆 | | |
| - Deckets for 14 tilted alosses (h 220 mm. diam | DNC 947040 D | | |


Baskets for 16 tilted glasses (h 220 mm - diam 100 mm) - blue

PNC 867040 □


PNC 867040 □



Front



Top



CWI

D


Cold Water inlet ΧD **Detergent connection** Chemicals inlet Electrical connection XR Rinse aid connection

EQ Equipotential screw

HWI

Hot water inlet WI = Water inlet

Side



Electric

Supply voltage:

505070 (NHT8G) 400 V/3N ph/50 Hz Convertible to: 230V 3~: 230V 1N~ 50Hz

Default Installed Power:* 9.9 kW Reducible Installed Power:* 6.9 kW **Boiler Heating Elements Power:*** 9 kW **Boiler Reducible To:*** 6 kW Tank heating elements: 3 kW Wash pump size: 0.8 kW

Water:

10-65°C Water supply temperature: Water supply hardness (MAX): 14°fH (8°dH) **Inlet Water supply pressure:** 0.5 - 7 bar Water consumption per cycle (It): 2

Boiler Capacity (It): 12 Tank Capacity (It): 24 G 3/4" Incoming water line size: Drain line size: 20.5 mm

Key Information:

N° of cycles: 3

Duration cycle - High productivity:* 57/84/150 sec.

Duration cycle - ETL Sanitation:* 45/84/150 sec.

1440

Racks per hour - High

productivity: 80

Racks per hour - ETL

Sanitation: * 63

Dishes per hour - High productivity: '

Dishes per hour - ETL

Sanitation: 3 1134

Wash temperature - High

productivity: 55-65 °C

Wash temperature - ETL

75 °C MIN Sanitation: Rinse temperature (MIN): 84 °C **External dimensions, Height:** 1549 mm **External dimensions, Width:** 746 mm **External dimensions, Depth:** 755 mm Net weight: 106 kg Shipping weight: 118 kg Shipping volume: 1.23 m³

Packaging size

746x755x1547 mm (WxDxH):

Noise level: <68 dBA

 * According to market standard, the productivity is declared at an inlet water supply temperature of 50°C . If the water is supplied at 65°C, the power can be reduced by 3 kW without any loss in productivity.

NOTE:

If the water supply temperature is less than 50°C, it is necessary to request higher power to maintain productivity.



