Hand held Mixers Speedy Mixer portable mixer 250 W Variable speed with Stainless Steel Tube



#### Hand held Mixers

Speedy Mixer portable mixer 250 W Variable speed with Stainless Steel Tube

600021 (SMVT20W25)

Portable mixer 250 W variable speed - stainless steel tube 200 mm - 230

V/1N/50-60

600022 (SMVT25W25)

Portable mixer 250 W variable speed - stainless steel tube 250 mm - 230 V/1N/50-60

# **Short Form Specification**

#### Item No.

Handheld mixer with stainless steel tube. To be used directly in stew pots. Motor unit and tube can be easily removed without tools to facilitate cleaning. Incorporates a convenient grip for less fatigue. Variable speed: up to 15000 rpm.

## **Main Features**

- Ideal to process small quantities (less than 35 lt).
- Very easy to use, convenient and ergonomic grip reduces fatigue while working.
- Delivered with:
  - -Choice of stainless steel tube: 200 mm or 250 mm, depending on model
  - -Cord and plug supplied as standard
- Its light weight ensures an optimum comfort for the user.
- Blade protection lip designed to offer a more efficient use and reduce work times.
- Easy to dismantle, the motor unit and the tube can be disassembled without the use of tools.
- Safety feature requires both hands to start the mixer (no volt release system).
- Light weight, ergonomic grip and adjustable speeds make preparation tasks fast and easy.

#### Construction

- Tube, knife and bell in stainless steel for an easier and safer cleaning process.
- Compact design, created to be used directly in stew pots even during cooking and ideal for small quantities.
- Variable speed from 2500 to 15000 rpm to make preparation tasks fast and easy.
- Motor protected from overload by a double insulation.
- Power: 250 watts.
- IPX3 protected.
- Tube and knife are dishwasher-safe.


# **Optional Accessories**

• Whisk tool for speedy mixer	PNC 650057
(variable speed models only)	

APPROVAL:



# **Hand held Mixers** Speedy Mixer portable mixer 250 W Variable speed with Stainless Steel Tube



## Electric

Supply voltage:

600021 (SMVT20W25) 230 V/1N ph/50/60 Hz 600022 (SMVT25W25) 230 V/1N ph/50/60 Hz

Electrical power: 0.25 kW Total Watts: 0.25 kW

## **Key Information:**

External dimensions, Height:

600021 (SMVT20W25) 470 mm 600022 (SMVT25W25) 520 mm External dimensions, Width: 110 mm External dimensions, Depth: 75 mm Shipping weight: 2 kg

El = Electrical connection **Equipotential screw** 

