



BAKERTOP

MIND Maps™

LONG Life 4!

Spare parts 4 years / 10.000 hours optional warranty*



CHALLENGE YOURSELF EVERY DAY. THE FIRST INGREDIENT FOR SUCCESS.

Excellence is served.

There is no room for error in bakery and pastisserie. Unox knows it and provides ovens and services that are designed to meet the most ambitious quality and business challenges.

It is an excellence you recognize at a glance. Made up of the same ingredients that your clients insist on: uncompromised quality, innovative and bold choices, proved and measurable efficiency and reliability.

Investing in innovation means seeing every day challenges in a whole new light: from giving value to every single gesture to the simplification of the entire production process. For you, this means maximum performance, freedom, ease of use and savings. For Unox, inventive simplification.





THE IDEA IN YOUR MIND, THE SO

Sign your baking

Controllable like your hand. Natural a
MIND.Maps™, the new line of profess
and the product you bake. With a ge

BAKERTOP MIND.Maps™ ONE and BA
baking process and maximum creati
costs. Outstanding performance in te

MIND.Maps™. Personality. In a ge

With Unox patented MIND.Maps™ tec
humidity and air speed on a visual la
process and draw it second by second

Try Unox MIND.Maps™. Add a touch



Innovation, quality, ease of use.
Unox technologies for BAKERTOP MIND.Maps™.



DRY.Maxi™

Minimum humidity.
Maximum flavour.

The patented DRY.Maxi™ technology rapidly removes humidity from the baking chamber and creates ideal conditions for food that needs to be baked in a completely dry environment. Oven baked products are soft, crisp and fragrant. You can bake whatever you like, with Unox, as it comes as standard.

AIR.Maxi™

Baking uniformity.
Quality without compromise.

The patented AIR.Maxi™ technology ensures a uniform distribution of the air and therefore of the heat throughout the baking chamber. Multiple auto-reversing high speed motors guarantee baking uniformity from top to bottom of the oven to those at the bottom of the oven to those at the top.

The possibility of choosing from 4 air speeds and 4 static modes allows any type of product to be baked perfectly, from the most delicate items to products that require high temperatures and a high rate of heat.

BAKERTOP MIND.Maps™ ONE

You rise to meet every challenge...

DON'T SELECT A BAKING PROGRAM. DRAW YOUR OWN.

The MIND.Maps™ visual language technology allows you to achieve even the most elaborate baking processes with a few simple hand-drawn gestures on the screen.

MAKE YOUR MASTER TOUCH REPEATABLE.

With MIND.Maps™ you can save all your baking processes and transform them into a patrimony of experience for all of your collaborators to use. Your touch of brilliance can be repeated as many times as you wish, at the touch of a button.

PUFF PASTRY, SPONGE CAKE, CHOUX PASTRY, CREAMS AND SO MUCH MORE.

Whatever baking method you wish to use and whatever level of humidity you need, DRY.Maxi™ and STEAM.Maxi™ regulate the humidity within the oven for results of the very highest quality.

ALWAYS DEMAND MAXIMUM QUALITY, WHATEVER THE LOAD.

AIR.Maxi™ technology distributes the air in a perfectly uniform manner. Whatever the load size you always have maximum quality and uniformity, from the lowest to the highest pan.

WORK IN A SAFE ENVIRONMENT.

Protek.SAFE™ insulation material keeps the external temperature of the oven at a safe working temperature.

DON'T WASTE YOUR TIME, OR YOUR TEAM'S TIME.

AIR.Maxi™ technology reduces the baking time by up to 40% compared to the previous BAKERTOP™ ovens. The Rotor.KLEAN™ automatic washing system together with DET&Rinse™ detergent leaves you with more free time to take on new challenges in the kitchen.

GET A FASTER RETURN ON YOUR INVESTMENT BY SAVING ENERGY.

The Spido.GAS+™ (only for PLUS models) and Protek.SAFE™ systems increase the efficiency of the baking process with the double advantage of respect for the environment and reduced running costs.

DEMAND A RELIABLE AND TIRELESS OVEN. JUST LIKE YOU.

Innovative yet dependable technologies combined with robust manufacturing details. Unox does not fear time and allows you to extend your product warranty* up to 4 years or 10.000 hours on-time. (*conditions apply, refer to www.unox.com for further details)



BAKERTOP MIND

... and exceed your o

CHALLENGE 1

DON'T SELECT
The MIND.Maps™ processes with

CHALLENGE 2

MAKE YOUR
With MIND.Maps™ your collabor

CHALLENGE 3

PUFF PASTRY
Whatever the STEAM.Maxi

CHALLENGE 4

ALWAYS DEM
AIR.Maxi™ always ha

CHALLENGE 5

WORK IN A
Protek.SAFE™ temperat

CHALLENGE 6

DON'T WASTE
AIR.Maxi™ washing sys

CHALLENGE 7

GET A FASTER
The Spido.GAS+™ process

CHALLENGE 8

DEMAND A
Innovative yet tireless to extend



CHALLENGE 9

WORK WITH AN INTELLIGENT
The ADAPTIVE.Cooking™ system parameters, records variation the best way to give you exa



MASTER.Touch ONE

The power of your creative instincts.



Revolutionary features in an intuitive design.
Creative freedom meets precision.

Having innovative technology, reliability and power at your fingertips is not enough.
To really make the difference you need to be able to use

MASTER.Touch P

The pleasure of being




Advanced features, rising to the challenge.

Conversing with an oven that is truly intelligent, that the results you are aiming for, monitors any the parameters during the baking process and s

BAKERTOP MIND.Maps™ COMBI OVENS.

A range of excellence.

16 600x400		10 600x400		6 600x400	
PLUS (ELECTRIC)					
	XEBC-16EU-EPR				
	16 600x400				
	80 mm				
	50 / 60 Hz				
	400 V ~ 3N				
Electrical power	35 kW				
	882x1043x1866				
	185 kg				
	XEBC-16EU-GPR				
PLUS (GAS)	16 600x400			XEBC-10EU-EPR	
	80 mm			10 600x400	
	50 / 60 Hz			80 mm	
	230 V ~ 1N			50 / 60 Hz	
	2,2 kW			400 V ~ 3N	
	G20, G25, G30, G31: 35kW			21 kW	
Dimensions (WxDxH mm)	882x1043x1866			860x957x1163	
	210 kg			130 kg	
	XEBC-16EU-E1R		XEBC-10EU-E1R		
	16 600x400		10 600x400		
ONE (ELECTRIC)	80 mm			80 mm	
	50 / 60 Hz			50 / 60 Hz	
	400 V ~ 3N			400 V ~ 3N	
	29,3 kW			14,9 kW	
Dimensions (WxDxH mm)	882x1043x1866			860x957x1163	
	185 kg			130 kg	
	XEBC-16EU-E1R		XEBC-10EU-E1R		
	16 600x400		10 600x400		
ONE (ELECTRIC)	80 mm			80 mm	
	50 / 60 Hz			50 / 60 Hz	
	400 V ~ 3N			400 V ~ 3N	
	29,3 kW			9,9 kW	
Dimensions (WxDxH mm)	882x1043x1866			860x957x1163	
	185 kg			130 kg	
	XEBC-16EU-E1R		XEBC-10EU-E1R		
	16 600x400		10 600x400		
ONE (ELECTRIC)	80 mm			80 mm	
	50 / 60 Hz			50 / 60 Hz	
	400 V ~ 3N			400 V ~ 3N	
	29,3 kW			9,9 kW	
Dimensions (WxDxH mm)	882x1043x1866			860x957x1163	
	185 kg			130 kg	
	XEBC-16EU-E1R		XEBC-10EU-E1R		
	16 600x400		10 600x400		
ONE (ELECTRIC)	80 mm			80 mm	
	50 / 60 Hz			50 / 60 Hz	
	400 V ~ 3N			400 V ~ 3N	
	29,3 kW			9,9 kW	
Dimensions (WxDxH mm)	882x1043x1866			860x957x1163	
	185 kg			130 kg	
	XEBC-16EU-E1R		XEBC-10EU-E1R		
	16 600x400		10 600x400		
ONE (ELECTRIC)	80 mm			80 mm	
	50 / 60 Hz			50 / 60 Hz	
	400 V ~ 3N			400 V ~ 3N	
	29,3 kW			9,9 kW	
Dimensions (WxDxH mm)	882x1043x1866			860x957x1163	
	185 kg			130 kg	
	XEBC-16EU-E1R		XEBC-10EU-E1R		
	16 600x400		10 600x400		
ONE (ELECTRIC)	80 mm			80 mm	
	50 / 60 Hz			50 / 60 Hz	
	400 V ~ 3N			400 V ~ 3N	
	29,3 kW			9,9 kW	
Dimensions (WxDxH mm)	882x1043x1866			860x957x1163	
	185 kg			130 kg	
	XEBC-16EU-E1R		XEBC-10EU-E1R		
	16 600x400		10 600x400		
ONE (ELECTRIC)	80 mm			80 mm	
	50 / 60 Hz			50 / 60 Hz	
	400 V ~ 3N			400 V ~ 3N	
	29,3 kW			9,9 kW	
Dimensions (WxDxH mm)	882x1043x1866			860x957x1163	
	185 kg			130 kg	
	XEBC-16EU-E1R		XEBC-10EU-E1R		
	16 600x400		10 600x400		
ONE (ELECTRIC)	80 mm			80 mm	
	50 / 60 Hz			50 / 60 Hz	
	400 V ~ 3N			400 V ~ 3N	
	29,3 kW			9,9 kW	
Dimensions (WxDxH mm)	882x1043x1866			860x957x1163	
	185 kg			130 kg	
	XEBC-16EU-E1R		XEBC-10EU-E1R		
	16 600x400		10 600x400		
ONE (ELECTRIC)	80 mm			80 mm	
	50 / 60 Hz			50 / 60 Hz	
	400 V ~ 3N			400 V ~ 3N	
	29,3 kW			9,9 kW	
Dimensions (WxDxH mm)	882x1043x1866			860x957x1163	
	185 kg			130 kg	
	XEBC-16EU-E1R		XEBC-10EU-E1R		
	16 600x400		10 600x400		
ONE (ELECTRIC)	80 mm			80 mm	
	50 / 60 Hz			50 / 60 Hz	
	400 V ~ 3N			400 V ~ 3N	
	29,3 kW			9,9 kW	
Dimensions (WxDxH mm)	882x1043x1866			860x957x1163	
	185 kg			130 kg	
	XEBC-16EU-E1R		XEBC-10EU-E1R		
	16 600x400		10 600x400		
ONE (ELECTRIC)	80 mm			80 mm	
	50 / 60 Hz			50 / 60 Hz	
	400 V ~ 3N			400 V ~ 3N	
	29,3 kW			9,9 kW	
Dimensions (WxDxH mm)	882x1043x1866			860x957x1163	
	185 kg			130 kg	
	XEBC-16EU-E1R		XEBC-10EU-E1R		
	16 600x400		10 600x400		
ONE (ELECTRIC)	80 mm			80 mm	
	50 / 60 Hz			50 / 60 Hz	
	400 V ~ 3N			400 V ~ 3N	
	29,3 kW			9,9 kW	
Dimensions (WxDxH mm)	882x1043x1866			860x957x1163	
	185 kg			130 kg	
	XEBC-16EU-E1R		XEBC-10EU-E1R		
	16 600x400		10 600x400		
ONE (ELECTRIC)	80 mm			80 mm	
	50 / 60 Hz			50 / 60 Hz	
	400 V ~ 3N			400 V ~ 3N	
	29,3 kW			9,9 kW	
Dimensions (WxDxH mm)	882x1043x1866			860x957x1163	
	185 kg			130 kg	
	XEBC-16EU-E1R		XEBC-10EU-E1R		
	16 600x400		10 600x400		
ONE (ELECTRIC)	80 mm			80 mm	
	50 / 60 Hz			50 / 60 Hz	
	400 V ~ 3N			400 V ~ 3N	
	29,3 kW			9,9 kW	
Dimensions (WxDxH mm)	882x1043x1866			860x957x1163	
	185 kg			130 kg	
	XEBC-16EU-E1R		XEBC-10EU-E1R		
	16 600x400		10 600x400		
ONE (ELECTRIC)	80 mm			80 mm	
	50 / 60 Hz			50 / 60 Hz	
	400 V ~ 3N			400 V ~ 3N	
	29,3 kW			9,9 kW	
Dimensions (WxDxH mm)	882x1043x1866			860x957x1163	
	185 kg			130 kg	
	XEBC-16EU-E1R		XEBC-10EU-E1R		
	16 600x400		10 600x400		
ONE (ELECTRIC)	80 mm			80 mm	
	50 / 60 Hz			50 / 60 Hz	
	400 V ~ 3N			400 V ~ 3N	
	29,3 kW			9,9 kW	
Dimensions (WxDxH mm)	882x1043x1866			860x957x1163	
	185 kg			130 kg	
	XEBC-16EU-E1R		XEBC-10EU-E1R		
	16 600x400		10 600x400		
ONE (ELECTRIC)	80 mm			80 mm	
	50 / 60 Hz			50 / 60 Hz	
	400 V ~ 3N			400 V ~ 3N	
	29,3 kW			9,9 kW	
Dimensions (WxDxH mm)	882x1043x1866			860x957x1163	
	185 kg			130 kg	
	XEBC-16EU-E1R		XEBC-10EU-E1R		
	16 600x400		10 600x400		
ONE (ELECTRIC)	80 mm			80 mm	
	50 / 60 Hz			50 / 60 Hz	
	400 V ~ 3N			400 V ~ 3N	
	29,3 kW			9,9 kW	
Dimensions (WxDxH mm)	882x1043x1866			860x957x1163	
	185 kg			130 kg	
	XEBC-16EU-E1R		XEBC-10EU-E1R		
	16 600x400		10 600x400		
ONE (ELECTRIC)	80 mm			80 mm	
	50 / 60 Hz			50 / 60 Hz	
	400 V ~ 3N			400 V ~ 3N	
	29,3 kW			9,9 kW	
Dimensions (WxDxH mm)	882x1043x1866			860x957x1163	
	185 kg			130 kg	
	XEBC-16EU-E1R		XEBC-10EU-E1R		
	16 600x400		10 600x400		
ONE (ELECTRIC)	80 mm			80 mm	
	50 / 60 Hz			50 / 60 Hz	
	400 V ~ 3N			400 V ~ 3N	
	29,3 kW			9,9 kW	
Dimensions (WxDxH mm)	882x1043x1866			860x957x1163	
	185 kg			130 kg	
	XEBC-16EU-E1R		XEBC-10EU-E1R		
	16 600x400		10 600x400		
ONE (ELECTRIC)	80 mm			80 mm	
	50 / 60 Hz			50 / 60 Hz	
	400 V ~ 3N			400 V ~ 3N	
	29,3 kW			9,9 kW	
Dimensions (WxDxH mm)	882x1043x1866			860x957x1163	
	185 kg			130 kg	
	XEBC-16EU-E1R		XEBC-10EU-E1R		
	16 600x400		10 600x400		
ONE (ELECTRIC)	80 mm			80 mm	
	50 / 60 Hz			50 / 60 Hz	
	400 V ~ 3N			400 V ~ 3N	
	29,3 kW			9,9 kW	
Dimensions (WxDxH mm)	882x1043x1866			860x957x1163	
	185 kg			130 kg	
	XEBC-16EU-E1R		XEBC-10EU-E1R		
	16 600x400		10 600x400		
ONE (ELECTRIC)	80 mm			80 mm	
	50 / 60 Hz			50 / 60 Hz	
	400 V ~ 3N			400 V ~ 3N	
	29,3 kW			9,9 kW	
Dimensions (WxDxH mm)	882x1043x1866			860x957x1163	
	185 kg			130 kg	
	XEBC-16EU-E1R		XEBC-10EU-E1R		
	16 600x400		10 600x400		
ONE (ELECTRIC)	80 mm			80 mm	
	50 / 60 Hz			50 / 60 Hz	
	400 V ~ 3N			400 V ~ 3N	
	29,3 kW			9,9 kW	
Dimensions (WxDxH mm)	882x1043x1866			860x957x1163	
	185 kg			130 kg	
	XEBC-16EU-E1R		XEBC-10EU-E1R		
	16 600x400		10 600x400		
ONE (ELECTRIC)	80 mm			80 mm	
	50 / 60 Hz			50 / 60 Hz	
	400 V ~ 3N			400 V ~ 3N	
	29,3 kW			9,9 kW	
Dimensions (WxDxH mm)	882x1043x1866			860x957x1163	
	185 kg			130 kg	
	XEBC-16EU-E1R		XEBC-10EU-E1R		
	16 600x400		10 600x400		
ONE (ELECTRIC)	80 mm			80 mm	
	50 / 60 Hz			50 / 60 Hz	
	400 V ~ 3N			400 V ~ 3N	
	29,3 kW			9,9 kW	
Dimensions (WxDxH mm)	882x1043x1866			860x957x1163	
	185 kg			130 kg	
	XEBC-16EU-E1R		XEBC-10EU-E1R		
	16 600x400		10 600x400		
ONE (ELECTRIC)	80 mm			80 mm	
	50 / 60 Hz			50 / 60 Hz	
	400 V ~ 3N			400 V ~ 3N	
	29,3 kW			9,9 kW	
Dimensions (WxDxH mm)	882x1043x1866			860x957x1163	
	185 kg			130 kg	
	XEBC-16EU-E1R		XEBC-10EU-E1R		
	16 600x400		10 600x400		
ONE (ELECTRIC)	80 mm			80 mm	
	50 / 60 Hz			50 / 60 Hz	
	400 V ~ 3N			400 V ~ 3N	
	29,3 kW			9,9 kW	
Dimensions (WxDxH mm)	882x1043x1866			860x957x1163	
	185 kg			130 kg	
	XEBC-16EU-E1R		XEBC-10EU-E1R		
	16 600x400		10 600x400		
ONE (ELECTRIC)	80 mm			80 mm	
	50 / 60 Hz			50 / 60 Hz	
	400 V ~ 3N			400 V ~ 3N	
	29,3 kW			9,9 kW	
Dimensions (WxDxH mm)	882x1043x1866			860x957x1163	
	185 kg			130 kg	
	XEBC-16EU-E1R		XEBC-10EU-E1R		
	16 600x400		10 600x400		
ONE (ELECTRIC)	80 mm			80 mm	
	50 / 60 Hz			50 / 60 Hz	
	400 V ~ 3N			400 V ~ 3N	
	29,3 kW			9,9 kW	
Dimensions (WxDxH mm)	882x1043x1866			860x957x1163	
	185 kg			130 kg	
	XEBC-16EU-E1R		XEBC-10EU-E1R		
	16 600x400		10 600x400		
ONE (ELECTRIC)	80 mm			80 mm	
	50 / 60 Hz			50 / 60 Hz	
	400 V ~ 3N			400 V ~ 3N	
	29,3 kW			9,9 kW	
Dimensions (WxDxH mm)	882x1043x1866			860x957x1163	
	185 kg			130 kg	
	XEBC-16EU-E1R		XEBC-10EU-E1R		
	16 600x400		10 600x400		
ONE (ELECTRIC)	80 mm			80 mm	
	50 / 60 Hz			50 / 60 Hz	
	400 V ~ 3N			400 V ~ 3N	
	29,3 kW			9,9 kW	
Dimensions (WxDxH mm)	882x1043x1866			860x957x1163	
	185 kg			130 kg	
	XEBC-16EU-E1R		XEBC-10EU-E1R		
	16 600x400		10 600x400		
ONE (ELECTRIC)	80 mm			80 mm	
	50 / 60 Hz			50 / 60 Hz	
	400 V ~ 3N			400 V ~ 3N	
	29,3 kW			9,9 kW	
Dimensions (WxDxH mm)	882x1043x1866			860x957x1163	
	185 kg			130 kg	
	XEBC-16EU-E1R		XEBC-10EU-E1R		
	16 600x400		10 600x400		
ONE (ELECTRIC)	80 mm			80 mm	
	50 / 60 Hz			50 / 60 Hz	
	400 V ~ 3N			400 V ~ 3N	
	29,3 kW			9,9 kW	
Dimensions (WxDxH mm)	882x1043x1866			860x957x1163	
	185 kg			130 kg	
	XEBC-16EU-E1R		XEBC-10EU-E1R		
	16 600x400		10 600x400		
ONE (ELECTRIC)	80 mm			80 mm	
	50 / 60 Hz			50 / 60 Hz	
	400 V ~ 3N			400 V ~ 3N	
	29,3 kW			9,9 kW	
Dimensions (WxDxH mm)					

FEATURES		■ Standard	□ Optional	— Not available
MANUAL BAKING MODES				
Convection baking 30 °C - 260 °C				
Mixed steam and convection baking 35 °C - 260 °C, with STEAM,Maxi™ 30% to 90%				
Mixed humidity and convection baking 35 °C - 260 °C, with STEAM,Maxi™ 10% to 20%				
Steaming 35 °C - 130 °C with STEAM,Maxi™ technology 100%				
Dry air baking 30°C - 260 °C with DRY,Maxi™ technology 10% to 100%				
Core probe				
Delta T baking with core probe				
THERMAL INSULATION AND SAFETY				
Protek.SAFE™ technology: maximum thermal efficiency and working safety				
Protek.SAFE™ technology: fan impeller brake to contain energy loss at door				
Protek.SAFE™ technology: electrical power absorption related to the real needs				
Protek.SAFE™ technology: gas power absorption related to the real needs				
Protek.SAFE™ PLUS: triple glazed door				
HIGH PERFORMANCE PRESSURE BURNER				
Spido.GAS™ technology: suitable for G20 / G25 / G25.1 / G30 / G31 gas types				
Spido.GAS™ technology: high performance straight heat exchanger pipes for				

UNOX accessories.

The team makes the difference in the kitchen.


Developed for food service professionals, the Unox accessories increase and optimize the functionality of your kitchen, making it a well-equipped and versatile working environment.



Baking Essentials


The Baking Essentials pans and grids enrich your oven with new functions, allowing you to reduce costs and save space in the kitchen.

With these accessories, your BAKERTOP MIND:Maps™ can bake anything, from puff pastry to macaroons, from biscuits to choux pastry, from croissants to pizzas and leavened products.



Neutral and technological complementary equipment

The vast range of Unox complementary equipment allows you to take maximum advantage of the available space. You can create a multifunctional and versatile baking area with open stands of various heights, storage cabinets and complementary equipment. For example, you can choose the DeckTop, a modern static oven that allows you to combine modern and traditional baking.



Trolleys and baskets

The Unox trolleys and baskets allow you to prepare all the pans or plates to be cooked and load them into the oven in one safe and easy movement.

They are perfect for full loads, reducing the amount of time the door is open and limiting any heat loss to the environment.



Hoods

The ventless hoods clean, remove odours and cool down the fumes that exit from the chimneys. In addition, a suction system draws up the fumes when the door is open, meaning the installation of expensive ceiling hoods is no longer necessary.

For electric ovens only.



HACCP & Data Management

The correct application of HACCP procedures in the kitchen can be controlled in a simple and effective manner using the BlackBox function of the UNOX.Link kit. With OVEX.Net™ 3.0 software you can check via your mobile telephone, at any time, energy consumption data and statistics of all equipment (Near Field Communication).

With BAKERTOP MIND:Maps™ ovens the management costs are completely under your control.



UNOX-Care

UNOX-Care products keep your oven clean, protect it over time and reduce any maintenance costs.

The automatic washing system Rotor:KLEAN™ and DET&Rinse™ detergent together guarantee perfect hygiene and the ideal long-term upkeep of the oven and its components.

The AUTO:Pure limescale filter, standard on all BAKERTOP MIND:Maps™ ovens, automatically removes limescale from the water and means you no longer need to have an external filter. For particularly hard or dirty water Unox





INVENTIVE SIMPLIFICATION



INTERNATIONAL

UNOX S.p.A.

Via Majorana 22 / 35010 Cadoneghe (PD) Italy

Tel +39 049 8657511 / Fax +39 049 8657555

info@unox.com

EUROPE

ITALY

UNOX S.p.A.

E-mail: info@unox.it

Tel.: +39 049 86 57 513

CZECH REPUBLIC

UNOX DISTRIBUTION s.r.o.

E-mail: info.cz@unox.com

Tel.: +420 241 940 000

GERMANY

DUEX HANDELS GMBH

E-mail: info@unox-oefen.de

Tel.: +49 2951 98760

RUSSIAN COUNTRIES

UNOX RUSSIAN COUNTRIES

E-mail: info.ru@unox.com

Tel.: +7 985 33 77 597

+7 915 397 48 38

FRANCE

UNOX FRANCE s.a.s.

E-mail: info@unox.fr

Tel.: +33 4 78 17 35 39

TURKEY

UNOX TURKEY

E-mail: info.tr@unox.com

Tel.: +90 530 176 62 03

UNITED KINGDOM

UNOX UK Ltd

E-mail: info@unoxuk.com

Tel.: +44 1252 851 522

PORTUGAL

UNOX PORTUGAL

E-mail: info.pt@unox.com

Tel.: +351 918 228 787

SPAIN

UNOX PROFESIONAL ESPAÑA S.L.

E-mail: info.es@unox.com

Tel.: +34 900 82 89 43

SCANDINAVIAN COUNTRIES

UNOX SCANDINAVIAN COUNTRIES

E-mail: info.se@unox.com

Tel.: +46 (0)768 716 422

AMERICA

U.S.A. & CANADA

UNOX INC.

E-mail: infousa@unox.com

Tel.: +1 800 489 8669

MEXICO

UNOX MEXICO

E-mail: info.mx@unox.com

Tel.: +52 1555 4314 180

ASIA

ASIA PACIFIC COUNTRIES

UNOX (ASIA) SDN. BHD

E-mail: info.asia@unox.com

Tel.: +603-58797700

REPUBLIC OF SOUTH KOREA

UNOX SOUTH KOREA

E-mail: info.asia@unox.com

Tel.: +82 10 4354 2856

PHILIPPINES

UNOX PHILIPPINES

E-mail: info.asia@unox.com

Tel.: +63 998 541 3990

U.A.E.

UNOX MIDDLE EAST DMCC

E-mail: info.uae@unox.com

Tel.: +971 55 426 3167

AFRICA

SOUTH AFRICA

UNOX SOUTH AFRICA

E-mail: info.sa@unox.com

Tel.: +27 845 05 52 35

OCEANIA

AUSTRALIA

UNOX AUSTRALIA PTY LTD.

E-mail: info@unoxaustralia.com.au

Tel.: +61 3 9876 0803

L12459A1 - Printed: 06-2015

All images used are for illustrative purposes only.
All data indicated in this catalogue is subject to change and may be updated without notice.

www.unox.com

