



XFT195



Capacity Pitch Frequency Voltage Electrical power Dimensions Weight XFT195 4 600x400 75 mm 50 / 60 Hz 230 V~ 1N / 400 V~ 3N 6,5 kW 800x770x509 mm 49 kg





r	
	X
	and
ı	
ı	
ı	
1	
ı	
ı	
1	
1	
1	
1	
1	
П	
П	
1	
1	
1	
1	
1	
1	
1	
1	
1	
1	
1	
1	
1	
ı	
ı	
ı	
ı	
ı	
1	
1	
1	
1	
1	
1	
1	
1	
1	
1	
1	
1	
1	
1	
1	
1	
1	
1	
1	
1	
1	
1	
1	
1	
1	
1	
1	
ı	
1	
ı	
ı	
ı	
ı	
ı	
1	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
ı	
п	





	МАПС	DYNAMIC	CLASSIC	MANUAL HUM.
BAKING MODES			,	
Convection baking 30 °C - 260 °C	•	•	•	•
Mixed humidity and convection baking 48 °C - 260 °C	•	•	-	•
AIR DISTRIBUTION IN THE BAKING CHAMBER				
AIR.Plus technology: fans with reversing gear for models 600x400	•	•	•	•
AIR.Plus technology; fans with reversing gear for models 460x330	•	•	•	-
CLIMA MANAGEMENT IN THE BAKING CHAMBER				
DRY.Plus technology: quick extraction of the humidity from the baking chamber	•	•	•	•
$\ensuremath{STEAM.Plus}$ technology: injection humidity from 20 to 100%, settable from the control panel	•	•	-	-
STEAM.Plus technology: manual injection humidity	-	-	-	•
Pump that allows the oven to draw water from the tank (for models 460x330)	•	•	-	•
Solenoid valve that allows the connection between oven and water directly (for models 600x400)	•	•	-	•
PANS				
Pans aluminium flat (only for models 460x330)	•	•	•	•
AUXILIARIES FUNCTIONS				
99 baking programs memory, each one composed by 3 steps + pre-heating	•	•	•	-
Protek.SAFE™ technology: maximum thermal efficiency and working safety (cold door glass and external surfaces)	•	•	•	•
Visualization of the set and real values of time left to finish the baking program	•	•	•	•
Continuous functioning «INF»	•	•	•	•
Visualization of the set and real values of the baking chamber temperature	•	•	•	-
Temperature unit settable in °C or °F	•	•	•	-
DOOR OPENING				
Manual up-to-down door opening	-	•	•	•
Rightto-left door opening	•	-	-	-
Automatic door opening at the end of the baking program	•	-	-	-
TECHNICAL DETAILS				
Rounded baking chamber made of high resistant stainless steel for hygine and easy of cleaning	•	•	•	•
Halogen lights	•	•	•	•
Light weight - heavy duty structure using innovative materials	•	•	•	•
Proximity door contact switch (for models 600x400)	•	•	•	•
Proximity door contact switch (for models 460x330)	•	•	•	-
Autodiagnosys system for problems or brake down	•	•	•	-
Safety temperature switch	•		•	•